

ATTO ThunderLink® FC 3162

THUNDERBOLT™ 3 TO 16Gb FIBRE CHANNEL



ATTO Technology, Inc. Thunderbolt™ 3 to 16 Gb Fibre Channel adapters provide maximum throughput for high-bandwidth network connectivity for demanding IT and media & entertainment applications.

TECHNICAL FEATURES

- Dual 16Gb Fibre Channel ports
- (2) SFP+ LC optical modules included
- Supports 4K video file transfer and display simultaneously with dual 40Gb/s Thunderbolt 3
- Daisy chain up to five additional Thunderbolt technology enabled devices
- Backwards compatible with 20Gb/s and 10Gb/s Thunderbolt devices via legacy adapter
- MultiPath Director™ failover and load balancing
- Three year standard product warranty
- RoHS Compliant

INDUSTRY PROVEN TECHNOLOGY

ATTO Technology, Inc. has 30 years of experience developing first-to-market high performance and reliable storage connectivity solutions for customers. ATTO ThunderLink® Fibre Channel adapters now provide creative professionals using Thunderbolt™ enabled hosts, cost effective access to storage not previously available using FireWire or USB. The integrated family of ThunderLink adapters boasts an extensive list of customer design wins and certifications with respected industry partners.

FLEXIBLE CONNECTIVITY SOLUTIONS

With dual channel configuration and support for load balancing and failover, the 32Gb Fibre Channel adapters are an ideal solution for users looking to achieve the highest I/O and data throughput for advanced video and access to IT applications. ThunderLink 16Gb Fibre Channel adapters can support both local and storage area networks for Windows® 7 and later, and macOS® Sierra and later platforms, providing a single connectivity solution for customers.

PERFORMANCE ENGINEERED

Fibre Channel adapters are designed to provide fast, redundant and highly available connectivity to Fibre Channel storage, and are engineered to manage latency for real-time applications. ATTO exclusive Advanced Data Streaming (ADS™) technology provides controlled acceleration of data to deliver the highest consistent performance and reliable data transfers for video editing, digital audio, video on demand, or database applications. ATTO pays close attention to detail in board design and signal integrity to minimize transmission errors and data corruption. Specialized Fibre Channel drivers with support for multipathing make ATTO the premier choice for high-performance Fibre Channel storage area network (SAN) connectivity.

ADVANCED MANAGEMENT TOOLS

The easy-to-use ATTO ConfigTool™ features an intuitive GUI that simplifies the installation, management and monitoring of the adapter. With advanced troubleshooting and performance tuning capabilities, ConfigTool provides users with sophisticated diagnostics and the flexibility to control settings for specific applications.

ATTO ThunderLink® FC 3162

THUNDERBOLT™ 3 TO 16GB FIBRE CHANNEL

APPLICATIONS

ATTO Technology, Inc. ThunderLink® Fibre Channel adapters deliver high-performance and reliable connectivity solutions for the most demanding storage environments, including digital content creation, tape streaming and backup, rich content delivery, server clustering, and complex databases. ATTO ThunderLink FC 3162 adapters enable users to achieve the ultimate in I/O performance for real-time and transactional applications.

GENERAL FEATURES

- Auto negotiation to 16Gb, 8Gb and 4Gb
- Supports point-to-point and direct fabric/switch attach
- ANSI Fibre Channel: FC-FS, FCP, FC-AL, FC-AL2, FC-PLDA, FC-FLA
- Flash ROM for easy field upgrades
- FC Class 3 Support
- Buffer Credits: 81
- Supports FDMI and WMI
- Supports NPIV and Virtual Fabric

ADVANCED SOFTWARE FEATURES

- Adaptive load balancing

USER BENEFITS

- Superior performance for a wide range of applications
- Low power consumption
- Increased switch port availability
- Reduced cost per MB of data transferred
- Seamless integration into existing Fibre Channel SANs
- Support for virtualized server environments
- Extensive certification with SAN infrastructure components

MANAGEMENT TOOLS

- ATTO ConfigTool™ (w/GUI) management and configuration utility

THUNDERBOLT CABLING

- 40Gb/s cables are designated with a “3” marking
 - Active
 - 1M - 40 Gb/s performance
 - 2M - 40 Gb/s performance
 - Passive
 - .5M - 40 Gb/s performance
 - 1M - 20 Gb/s performance
 - 2M - 20 Gb/s performance

OPERATING SYSTEM SUPPORT

- macOS® Sierra and later
- Windows® 7 and later

DIMENSIONS

- 8.66”(D) x 4.07”(W) x 1.20”(H)

POWER ADAPTER

- Input: 100-240VAC, 50-60Hz, 0.6A Max
- Output: 12VDC

EXTERNAL CONNECTIVITY

- Dual (2) 16Gb SFP+ LC Optical modules
- External LEDs for on-line and speed status for each port

ENVIRONMENTAL

OPERATING TEMPERATURE:

- Temperature: 0-36° C at 10,000 ft, 40° C at 6,000ft
- Humidity: 10-90% non-condensing

STORAGE TEMPERATURE:

- Temperature: -40 C to 70° C
- Humidity: 5-95% non-condensing

COMPLIANCE

- FCC Part 15, Subpart B, Class B
- EN55022, Class B/EN55024
- EN60825-1
- EN60825-2
- EN60950-1
- cTUVus
- EU RoHS (2011/65/EC)
- TAA Compliant (country of origin: USA)

WARRANTY

- Three Years

ORDERING INFORMATION

- Phone: 716-691-1999

THUNDERBOLT 3 TO 16GB FIBRE CHANNEL

- ThunderLink FC 3162: TLFC-3162-D00
- ThunderLink FC 3162: TLFC-3162-DE0 (CMEA)

COMPLEMENTARY PRODUCTS

- ATTO Celerity™ Fibre Channel HBAs
- ATTO ExpressSAS® HBAs and RAID adapters
- ATTO FastFrame™ NICs
- ATTO FibreBridge® Fibre Channel bridges
- ATTO premium cables



ATTO ThunderLink	FC 3162
Model Number	TLFC-3162-D00 (US) TLFC-3162-DE0 (UK/EMEA)
Input Connectors	(2) 40Gb/s Thunderbolt™
Output Connectors	(2) 16Gb/s Fibre Channel
Connector Type	SFP+ LC Optical
Form Factor	Desktop
Warranty	3 Year